

PCI / ISA SDLC adapter

The best-selling SDLC card in Taiwan

This highly acclaimed PCI/ ISA SDLC adapter remains as the most popular product after 20 years of development, and is already adopted by various banks, famous ATM manufactures and numerous customers in Taiwan, China and Japan.

Numerous versions of firmware are available to support PCI/ ISA SDLC adapter working under different network conditions or host machines.



Specification

Controller: Z8530
Serial Port: One
Serial Interface: V.35, RS-232
Serial Data Format: BCS, SDLC, HDLC
Data Rate: Up to 64kbps
Clocking: Internal/ External
Temperature: 0~50 degrees celsius
Humidity: 0~95%
noncondensing Altitude: -200 to +10,000 ft.
Mechanical: Standard PCI/ ISA card
Power Requirement: 0.8A+5V, 25mA+12V, 25mA-12V
Connector: DB-25(male)
Cable Options: DB-25(female) to DB-25(male)
DB-25(female) to 34-pin V.35(male)

Features

- On-board CPU
- Single API entry
- Multi-protocol support: SDLC / HDLC / BSC
- Microsoft Windows support: 95 / 98 / 2000 / XP / 2003 / Vista
- Line speed automatic detection
- LED line status displays
- Automatic connection recovery function
- Connection status monitor software supported
- Easy setup procedure

SYSTEMEX COMM

www.systemexcomm.com